



TEL. +41 (0)91 9945545 - FAX. +41 (0)91 9942260 - e-mail: info@interbox.ch - www.interbox.ch

LARGE CONTAINERS / LOGISTICS AND HANDLING

CARGOPALLET 600 PLUS GRATING











The CARGOPALLET 600 PLUS GRATING is versatile and sturdy, has good structural rigidity, resists deformation. Ideal for food industry, pharmaceuticals, mechanical, rubber treatment and plastics industries. The stacking of Cargopallet 600 Plus grating is assured by 4 cylinder/spherical pins obtained directly from the mold on top of the container that fit into appropriate seats at the bottom of the legs/runners of container. The 35 mm recessed ensure maximum safety and stability of the stacking. Easy to clean, does not absorb smells or damp and can be stored at open. Fitted with feet, runners or wheels, can be shifted with a transpallet or a forklift truck. The four runners version is suitable to meet heavy duty loads and working conditions. The support along the entire perimeter allows among other things, its use on roller conveyors without risk of hindrance or stumbling where there are curves or exchange points.

Maximum capacity: 550 dm3

Max load capacity: 500 kg with evenly distributed load - in piling: 2000 kg, standing on the floor by feet or runners.

Versions: With 4 feet, with 2 runners, with 4 wheels, 2 runners and 4 wheels.

Accessories: Lids, label holder, ball valve, screw plug.

Material: PP RPP Inert to acids, hydrocarbons, alkalis and solvents.

Size

ARTICLE	EXTERNAL SIZE mm			INTERNAL SIZE mm		
	Α	В	Н	Α	В	Н
CARGOPALLET 600 PLUS - Grating + 4 feet	1200	800	850	1130	725	690
CARGOPALLET 600 PLUS - Grating + 2 or 4 runners	1200	800	850	1130	725	690
CARGOPALLET 600 PLUS - Grating + 4 wheels	1200	800	1000	1130	725	690
CARGOPALLET 600 PLUS - Grating + 2 runners and 4 wheels	1200	800	1000	1130	725	690
Height of feet			120			
Gap between feet	830	600				
Wheelbase between the 2 cylinder/spherical pins	1120	720				
The selection is at your disposal to advise the your impact quited to your peeds						